CENTRAL INTELLIGENCE AGENCY

INFORMATION REPORT

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited

COUNTRY								
	East Germany		REPORT					
SUBJECT	East German Tu	be Specifications	DATE DISTR. 15 July 1955					
			NO. OF PAGES	2				
PATE OF INFO.			REQUIREMENT NO.	RD				
LACE ACQUIRED			REFERENCES	25>	X 1			
		This is U	NEVALUATED Informat	ion				
A CONTRACTOR OF THE CONTRACTOR	THE S	OURCE EVALUATIONS IN THIS REPO	ORT ARE DEFINITIVE.	The desiration and angular materials and the control control of the control of th				
		THE APPRAISAL OF CONTENT IS (FOR KEY SEE REVERSE	TENTATIVE.	2	25X′			
	ne tube is still	the VEB Funkwerk Erfur, and the VEB Werk fue under development; subminiature low-fr	rt (E), the VEB Roehr er Fernmeldewesen (WF		5X1			
DL-193 DC-90 DL-94 EA-960/ EC-84 (6 EC-92/U EC-94 (6	AJ4) (WF) C-92 (E) AF4) (WF) L-81	subminiature output high and low freque mixer, oscillator, power pentode * ultra-short-wave di high mu triode for high mu triode for switching, oscillat high mu ultra-short oscillator *	ancy amplifier pentode and amplifier pentode ode for measuring * ultra-short-wave ampl getter, neutralized of or and mixer * -wave triode for addi	lifying * cathode, and cascade itive mixing and	•			
DL-193 DC-90 DL-94 EA-960/ EC-84 (6 EC-92/U EC-94 (6 EL-81/P (21A6) (1	(N) (E) (E) (961(E) AJ4)(WF) C-92(E) AF4)(WF) L-81 WF) Y-81 (E)	subminiature output high and low freque mixer, oscillator, power pentode * ultra-short-wave di high mu triode for high mu triode for switching, oscillathigh mu ultra-short oscillator * output pentode (for control { Zeilenable power rectifier switching switching)	t pentode * ency amplifier pentode and amplifier pentode .ode for measuring * ultra-short-wave ampl getter, neutralized o or and mixer * -wave triode for addi final stage of line- enksteuerung) * tch diode for super a	lifying * cathode, and cascade tive mixing and deflecting (sweep)				
DL-193 DC-90 DL-94 EA-960/ EC-84 (6 EC-92/U EC-94 (6	(N) (E) (E) (961(E) AJ4)(WF) C-92(E) AF4)(WF) L-81 WF) Y-81 (E) (WF)	subminiature output high and low freque mixer, oscillator, power pentode * ultra-short-wave di high mu triode for high mu triode for switching, oscillat high mu ultra-short oscillator * output pentode (for control { Zeilenabl power rectifier swifull-wave rectifier high mu high-freque:	t pentode * ency amplifier pentode and amplifier pentode .ode for measuring * ultra-short-wave ampl getter, neutralized cor and mixer *wave triode for addi final stage of line- enksteuerung) * tch diode for sweep ency pentode with high	lifying * cathode, and cascade itive mixing and deflecting (sweep) ircuit *				
DL-193 DC-90 DL-94 EA-960/ EC-84 (6 EC-92/U EC-94 (6 EL-81/P: (21A6) (1 EY-81/P:	(N) (E) (E) (961(E) AJ4)(WF) C-92(E) AF4)(WF) L-81 WF) Y-81 (E) (WF)	subminiature output high and low freque mixer, oscillator, power pentode * ultra-short-wave di high mu triode for high mu triode for switching, oscillat high mu ultra-short oscillator * output pentode (for control { Zeilenabl power rectifier swifull-wave rectifier high mu high-frequeinitial stage in brahigh-frequency pentores.	t pentode * ency amplifier pentode and amplifier pentode .ode for measuring * ultra-short-wave ampl getter, neutralized cor and mixer *wave triode for addi final stage of line- enksteuerung) * tch diode for sweep co ncy pentode with high odd-band amplifying ode with high durabil	lifying * cathode, and cascade dive mixing and deflecting (sweep) freuit * durability for				
DL-193 DC-90 DL-94 EA-960/ EC-84 (6 EC-92/U EC-94 (6 EL-81/P (21A6) (1 EY-81/P 5Z4C 6AC7(k)	(N) (E) (E) (961(E) AJ4)(WF) C-92(E) AF4)(WF) L-81 WF) Y-81 (E) (WF)	summiniature output high and low freque mixer, oscillator, power pentode * ultra-short-wave di high mu triode for high mu triode for switching, oscillat high mu ultra-short oscillator * output pentode (for control { Zeilenable power rectifier swifull-wave rectifier high mu high-frequent initial stage in broad-band ultra-short-wave per scanning tube (Bildufor direct observatiscanning tube with i	t pentode * ency amplifier pentode and amplifier pentode defor measuring * ultra-short-wave ampl getter, neutralized of or and mixer * -wave triode for addi final stage of line- enksteuerung) * tch diode for sweep of ncy pentode with high oad-band amplifying ode with high durabil amplifying	lifying * cathode, and cascade live mixing and deflecting (sweep) ircuit * durability for ity for the final ision equipment) * r television receivers mg rester				

25 YEAR RE-REVIEW

STATE	X	ARMY	X	NAVY	X	AIR	T x	FBI	T-T-			 	
£				****			1	1 .01	<u></u>	AEC	-	 	25X
		tribution ind		'X"; Field	distribution	by "#".	.)					 	

25X1

